

thermoscientific



Revolutionary solvent evaporation complete laboratory workflow

Thermo Scientific Rocket Synergy Evaporator

ThermoFisher
SCIENTIFIC

Sample evaporation with walk-away capability to produce uncompromised results

The Thermo Scientific™ Rocket™ Synergy Evaporator is for laboratories seeking to spend minimal time and effort to concentrate or dry large-volume samples for chromatographic analysis.

Concentrates or dries up to 18 ASE vials or 6 large-volume flasks unattended.

Developed as a result of users' demands for an evaporator that could quickly process large-volume samples in parallel without supervision, the Rocket Synergy Evaporator can concentrate or dry 18 ASE vials or up to 6 large-volume 450 mL flasks.

This enables the user to focus on other tasks, confident that the Rocket Synergy Evaporator will achieve reproducible evaporation with excellent recovery rates.

- Five times faster than conventional sample evaporators
- Substantially greater productivity than rotary evaporators
- True walk away capability with no supervision required
- Eliminate manual sample transfer steps between cleanup and analysis
- Genevac AutoStop feature for end point detection
- Powerful centrifuge that eliminates solvent bumping

The Rocket Synergy Evaporator is equipped with the advanced performance features that our users expect, such as automated end point detection, effective bumping protection, accurate temperature regulation, and easy-to-use controls.

A two-stage cold trap is built into the Rocket Synergy Evaporator, providing high levels of solvent recovery, even with volatile organic solvents. The cold trap auto-drains is under the control of the evaporator to ensure that high solvent recovery is maintained, no matter what mix of solvents are being used.

The Rocket Synergy Evaporator has proven to yield fast, unattended operation that significantly improves laboratory productivity.

Why compromise analytical results with cumbersome and ineffective sample evaporation procedures?




Innovative Sample Preparation Solutions to Optimize Laboratory Workflow

Sample preparation is the most vital part of the laboratory workflow. Since greater than 60% of all errors occur during this phase, it is often considered the most frustrating and cumbersome component of the workflow. While analytical technology has evolved remarkably over the last 20 years, most sample preparation still relies on antiquated manual techniques that can produce low analyte recovery with highly variable reproducibility. A traditional sample preparation workflow consists of extraction, cleanup, and evaporation, all of which use manual sample transfer steps through the transition. Techniques such as Soxhlet, gel permeation chromatography, and nitrogen blowdown evaporation often produce total sample prep workflow times in excess of 60 hours per batch. In 1995, the Thermo Scientific™

Dionex™ ASE™ Accelerated Solvent Extractor system was introduced and substantially reduced the time but did not address clean up or evaporation. More recently, we introduced the Dionex ASE system with In-Cell Cleanup and Rocket Synergy Evaporator to address the entire sample preparation workflow and reduce the total time to six hours per sample batch.

The combination of the Dionex ASE system with In-Cell Cleanup and the Rocket Synergy Evaporator provides a total sample preparation solution for the analytical laboratory. The combination of these two techniques entirely eliminates both the cleanup step and manual sample transfer. The effect of this combination on laboratory productivity is profound and ensures highly accurate and reproducible sample preparation.

Sample Preparation Productivity *



*average processing times for 18 samples



Dionex ASE 350 Accelerated Solvent Extractor System



Rocket Synergy Evaporator



Thermo Scientific™ TRACE™ 1300 Series GC

Inside the Rocket


The Rocket Synergy Evaporator uses a new technology that works as follows:

Samples are loaded into the rotor, spun, and placed under vacuum (point B). The centrifugal force generated by spinning the centrifuge rotor creates a pressure gradient within the solvent contained in the vials. The samples boil from the top down, helping to prevent any bumping. Dri-Pure technology prevents any bumping and cross contamination.

To achieve fast evaporation and precise temperature control, a low temperature, and low pressure steam is used to heat the samples indirectly. The steam condenses on the flasks/tubes, which are cold due to the solvent(s) boiling inside them. Condensate is thrown off the spinning flask, where it is recycled and boiled again to make more steam.

Steam temperature is controlled in two ways: 1) The pressure in the outer chamber (at point A) is set to boil water at the desired temperature, while 2) The temperature of the outer chamber is precisely controlled at or below the set temperature.

To ensure that steam does not enter the samples, each tube or flask slides effortlessly into the rotor, and the action of spinning the rotor firmly clamps it in place.



Controls

The controls of the Rocket Synergy Evaporator are easy to use: highlight the desired evaporation or concentration method using the right hand knob, and start. The left hand knob activates the (optional) on-board strobe. Rotating the strobe knob adjusts the strobe frequency and allows each of the six positions to be viewed separately in real time.

The software controlling the evaporation process can be optimized for each customer application and new methods created to enhance performance, usually in partnership with your local Thermo Fisher Scientific representative. New methods are supplied by email and uploaded using a USB key. Data is downloaded in the same way.



Choice of formats for the best results

The Rocket Synergy Evaporator can be used either to dry samples completely, or to concentrate them to a small volume. To help achieve the best results in the desired sample format, there are several options, described below:



1 Puck for ASE Vials

The Rocket Synergy Evaporator accommodates the direct transfer of up to 18 ASE vials. Each 60 mL vial can be directly transferred from the Dionex ASE system and loaded into the Puck for evaporation.

2 Flip-Flop System

Extracts are collected in the Dionex ASE system using a double-ended 60 mL vial. An adaptor with a GC autosampler vial is then fitted. The 60 mL vial is flipped over and placed into the Puck in the Rocket Synergy Evaporator and the cap is removed. The samples are concentrated directly into the GC vial.

3 Thermo Scientific™ Rocket™ Evaporator SampleGenie™ for GC Vials

Allows concentration of the sample directly into a GC autosampler vial. The vial is insulated so that only the solvent in the flask evaporates, leaving a small volume in the vial.


4 SampleGenie 4 Flasks

Allows concentration of sample into a 20 mL scintillation vial or a 4 Dram vial. Accommodates vials from 12mm to 28 mm in diameter and up to place 70 mm on the same line.


5 Evaporation Flasks

450 mL flasks that are used for drying or concentrating samples.

Uncompromised Analyte Recovery Excellent Reproducibility



% analyte recovery for common PAHs following evaporation using both the Rocket Synergy Evaporator and nitrogen blowdown (n = 6). The Rocket Synergy Evaporator consistently generated higher % recoveries following evaporation. Extractions were performed from spiked soil using the Dionex ASE 350 system.



% RSD for repeat evaporations of PAH samples using both the Rocket Synergy Evaporator and nitrogen blowdown. % RSD ranged from 1-2% for Rocket Synergy Evaporator samples (n=6) and from 3-11% for nitrogen blowdown samples (n=6).

Evaporation Times*

	100 mL	250 mL	400 mL
DCM (dichloromethane)	35 min	1 h	1 h 10 min
Methanol	1 h 10 min	2 h	2 h 30 min
DMF	45 min	1 h 15 min	1 h 40 min
Water	2 h 40 min	4 h 30 min	5 h 30 min
Water/ACN (1:1)	3 h	5 h	6 h 15 min

The Rocket Synergy Evaporator efficiently evaporates solvents commonly used with the Dionex ASE system.

*Times are given for complete dryness for 6 flasks simultaneously evaporated

Solvent Recovery

Solvent	Recovery
DCM	80%
DMF	99%
Ethanol	99%
Methanol	98%
Water	99%
Water/acetonitrile	98%

The Rocket Synergy Evaporator is eco-friendly green technology. Vapors from solvents commonly used with the Dionex ASE system are condensed and trapped for appropriate disposal.

Total Workflow Solutions from Thermo Scientific



Dionex ASE 150/350 Systems
Automated accelerated solvent extractor systems. Enables extraction of solid and semisolid samples using common solvents at elevated temperatures and pressures.



Thermo Scientific™ TSQ™ 9000 Evo Triple Quadrupole GC-MS/ MS System

A reliable, easy-to-use system that enables faster, more precise, error-free analyses, saving time and reducing laboratory costs. It enables more precise routine analyses and offers unstoppable productivity with uncompromised MS/MS simplicity.



Rocket Synergy Evaporator
A revolutionary solvent evaporator that concentrates or dries up to 18 ASE tubes or 6 large-volume flasks unattended.



**Thermo Scientific™ Dionex™
AutoTrace™ 280 Solid-Phase
Extraction (SPE) Instrument**
Automated SPE instrument that extracts large-volume samples (20 mL-20 L) for the isolation of trace organics in aqueous matrices. Produces analyte recoveries that are superior to manual liquid-liquid extraction techniques using less time and solvent.



Thermo Scientific™ Vanquish™ and UltiMate™ 3000 LC Systems

Thermo Scientific Vanquish UHPLC systems are the most advanced UHPLC instruments available: designed from the ground up to improve performance and repeatability with no trade-offs in quality, robustness, or ease-of-use. The UltiMate 3000 HPLC series provides excellent chromatographic performance while maintaining easy-to-use, reliable operation.



**Thermo Scientific™ TRACE™
1300 Series GC Systems**
The first and only gas chromatograph featuring user-exchangeable miniaturized, instant connect injectors and detectors that eliminate maintenance downtime and enable the user to quickly tailor instrument capability to specific applications and daily workload.



Thermo Scientific™ Dionex™ Chromeleon™ Chromatography Data System Software

One scalable software platform for LC, GC, IC and MS that provides Operational Simplicity™ by streamlining your entire analysis process – ultimately boosting your lab's overall productivity and increasing the quality of your analytical results.

Find out more at thermofisher.com/chromatography

For Research Use Only. Not for use in diagnostic procedures. © 2019 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries. This information is presented as an example of the capabilities of Thermo Fisher Scientific Inc. products. It is not intended to encourage use of these products in any manners that might infringe the intellectual property rights of others. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details. **BR70315-EN 0519S**

ThermoFisher
SCIENTIFIC